

Product Name

Aspect Glass™ Decorative Tiles
OmniClass 2004: Table 22-09 30 29 – Glass Tiling

**Associated Specification Section**

MasterFormat 1995: Section 09370 – Glass Tile
MasterFormat 2004: Section 09 30 29 – Glass Tiling

Manufacturer's Name

Acoustic Ceiling Products, L.L.C.

July, 2015

PRODUCT DESCRIPTION**PRODUCT FEATURES**

- **BASIC USES/RELATED USES**
 - Interior decorative tile.
 - Architectural tile for decorative wall surfaces, backsplashes and other applications.
 - Custom architectural and décor applications.
- **PRODUCT ATTRIBUTES AND CHARACTERISTICS**
 - Artisan Glass for decorative Architectural feel.
 - Tiles are manufactured using a color infused process.
 - Easily cut with normal glass cutting tools common to ceramic and stone industries, such as table wet saws.
 - Self-adhesive, bonding adhesive or tape adhesive applied.
- **SELECTION CRITERIA**
 - Tile can be attached with adhesive, eliminating need for exposed fasteners or alternately, retaining fasteners can be used.
 - Tiles provide an alternative to other glass or ceramic tile installation that uses mastics and post grouting leaving clean designer look.
- **APPLICABLE STANDARDS, RELATED REFERENCES**
 - ASTM E84 - Standard Test Method for Surface Burning Characteristics of Building Materials.
- **QUALITY STATEMENT, TESTS, CERTIFICATIONS, AND APPROVALS**
 - Material meets or exceeds ASTM E84 for Class 1 and Class A materials.
- **PACKAGING, HANDLING, PROTECTION, AND DELIVERY INSTRUCTIONS**
 - Store tiles flat, in a clean, dry area with consistent temperatures to avoid condensation and moisture collection.
 - During handling, do not slide tiles against each other or over rough surfaces.
- **MANUFACTURER'S WARRANTY**
 - Warranty: Manufacturer's limited warranty: Five (5) years.
- **LIMITATIONS**
 - Glass tiles must be attached to a substrate such as primed drywall, plaster or clean, smooth tile.

Product Name

Aspect Glass™ Decorative Tiles
OmniClass 2004: Table 22-09 30 29 – Glass Tiling

**Associated Specification Section**

MasterFormat 1995: Section 09370 – Glass Tile
MasterFormat 2004: Section 09 30 29 – Glass Tiling

Manufacturer's Name

Acoustic Ceiling Products, L.L.C.

July, 2015

PRODUCT DESCRIPTION

- Note: we recommend a primer/sealer prior to installation to eliminate a good bond to substrate.
 - Adhesive attachment must ensure full contact with the glass face.
 - Care must be taken to avoid damaging the polished glass finish during cutting.
 - Material can be cut with a glass wet saw.
- SAFETY PRECAUTIONS
 - De-bur sharp edges after cutting with fine surfaced grit sand paper sponge.
- AVAILABILITY
 - Nation wide
- COST
 - Varies with size of tile/s, substrate condition and configuration, and relative size of building.
 - Consult manufacturer's national or regional offices for specific product costs or relative costs.

PRODUCT PROPERTIES

- MATERIALS, COMPOSITION, AND PROPERTIES
 - Melt Glass material :
 - Glass Tile: 0.4 mm (.016 inch).
- ACCESSORIES
 - Adhesives :
 - PB-FSA High Performance Acrylic Adhesive recommended for peel and stick tile.
 - One-component, high strength construction adhesives, silicones and urethanes as recommended by product manufacturer for panels.
 - Tape: Double sided foam tape with contact surfaces, as recommended by panel manufacturer.
- DIMENSIONS
 - Available Tile Thicknesses: 4 mm (0.016 inch)
 - Tile Sizes: 76 x 152 mm (3 x 6 inches) (Matted)
- SHOP FABRICATION AND ASSEMBLY
 - Shop cutting of custom sizes.

Product Name

Aspect Glass™ Decorative Tiles
OmniClass 2004: Table 22-09 30 29 – Glass Tiling

**Associated Specification Section**

MasterFormat 1995: Section 09370 – Glass Tile
MasterFormat 2004: Section 09 30 29 – Glass Tiling

Manufacturer's Name

Acoustic Ceiling Products, L.L.C.

July, 2015

PRODUCT DESCRIPTION

- **COLORS AVAILABLE**

- Color: [Sunlit Meadow, Wild Strawberry, Morning Dew, Fresh Sage, Storm Cloud, Sienna Bark, Frost, Glacier, Leather, Steel, Ebony, and Putty.]

PRODUCT PLACEMENT

- **PREPARATION**

- Ensure substrate surfaces are clean, dry, smooth and free from dust, grease, or wax.
- Use isopropyl-alcohol two-cloth cleaning method as a minimal surface preparation for all adhesive or tape bonding.
- Prime substrate with one coat of a high-quality 100% acrylic-based, (not PVA-based) primer/sealer.
- Clean existing ceramic or hard surface tile substrate well; generally primer may not be required.
- Measurement and Lay-out:
 - Measure first area to be covered; lay-out first tile. Using a temporary marker, transfer measurements to first tile.
 - To fit around pipes and other irregularities or interruptions, transfer cutting lines to the tile using a cardboard pattern as a guide.

- **CUTTING**

- Cut using a proper glass tile diamond tip wet saw or other glass cutting tool.
- Use a fine-grit sandpaper sponge to deburr/polish edges of newly cut tiles.

Product Name

Aspect Glass™ Decorative Tiles
OmniClass 2004: Table 22-09 30 29 – Glass Tiling

**Associated Specification Section**

MasterFormat 1995: Section 09370 – Glass Tile
MasterFormat 2004: Section 09 30 29 – Glass Tiling

Manufacturer's Name

Acoustic Ceiling Products, L.L.C.

July, 2015

PRODUCT DESCRIPTION**APPLICATION**

- Apply tiles from inside corner, working outwards and upwards.
- If designing layout of tiles to be centered at a focal point, such as behind a sink or stove area, build out from both sides of the focal point, symmetrically.
- For self-adhesive tiles, peel backing from tile and align into correct position.
- With a soft cloth, apply pressure evenly across the tile and squeeze out excess air when applying.

● SAFETY INSTRUCTIONS

- Do not stand or walk on release paper or tile with release paper to avoid slipping or falling.

Corporate Identification

Acoustic Ceiling Products, L.L.C.
P.O. Box 1581
Appleton, WI, U.S.A. 54912-1581
Phone Toll Free: 1-800-434-3750
Fax Toll Free: 1-800-434-3751
Web site: www.acpideas.com
E-mail to: techsupport@acpideas.com

Technical Services Available

Technical Support: 1-800-558-0615

Classification and Filing

MasterFormat 2004:
Section 09 30 29 – Glass Tiling

MasterFormat 1995:
Section 09370 – Glass Tile

OmniClass 2004:
OmniClass 2004: Table 22-09 30 29 – Glass Tiling
Table 23-35 10 14 – Wall Tiles

UniFormat 1998:
C30 Interior Finishes
C3010 – Wall Finishes

END